

SHORT PACKER WITH METAL CORE and CHASSIS

KISA METALLİ BORU TAMİR KÖRÜĞÜ



Part Number Ürün Kodu	Nominal Size Nominal Ebat	Cylinder Length Silindir Uzunluğu (mm)	Min. Contact Min. Kontak (mm)	Required Inflation Pressure Çalışma Basıncı (bar)	Product Diameter Ürün Çapı (mm)	Product Total Length Ürün Uzunluğu (mm)	Bypass Diameter Baypass Çapı (mm)	Product Weight Ürün Ağırlığı (kg)
SP150200	150 - 200	780	580	2	110	1020	65	6,5
SP250300	250 - 300	780	600	2	190	1080	150	13
SP300400	300 - 400	800	525	1,5	240	1100	200	16
SP350450	350 - 450	800	550	1,5	285	1100	245	19
SP500600	500 - 600	900	450	1,5	445	1200	400	30

Short packers have a replaceable double-layer rubber sleeve mounted on a PU tube. All other parts installed in a packer are made of corrosion resistant materials. On one side of the packer three wheels are attached at an angle of 120° to prevent tipping over while transported along the pipeline. The effective packer length is 600 mm therefore they are suitable for repair of pipeline joints or repair of shorter pipeline sections along with insertion of stainless steel shells.